

D2488B



Specifications-Technical Data

Engine	Kubota V3800 TIEF4 115 HP Turbo Diesel	Fuel Capacity	19 Gal (US) Approx.8 Hrs. Run Time
Drive System	Tandem pump, closed loop, two speed	Towing Capacity	10,000 Lbs.
Water Propulsion	Hydraulically Driven Dual 10” Bronze Props	Ground Pressure	1.6 PSI unloaded; 2.3 PSI loaded
Tri-Mode Drive	Wheels Only, Props Only or Props & Wheels	Hyd. Tank Capacity ...	13 Gal (US); Mobil DTE 10 Excel 46
Electrical System	12 Volt with 90 Amp Alternator	Unit Dry Weight	8,400 Lbs.
Battery	Optima Blue Top 800 CCA	Payload Capacity	Land 3,000 Lbs; Water 1,600 Lbs
Park/Emergency Brake ...	Hydraulic parking braking system	Seating	up to 8 Persons
Instrumentation	Marine Grade Components	Land Speed	up to 15 MPH
Body Construction	3/16” and 1/8” Full-Weld Aluminum.	Speed in Water	up to 3.3 MPH
Bilge Pump	2200 GPH 12 Volt with Auto/Man. Switch	Ground Clearance ...	27” (Center)
Hydraulic Oil Cooler	Triple Hydraulic Cooler	Tracks	24” Industrial Rubber; Over-the-Tire

* Specifications are subject to change with added options and model updates *

* August 2020

Engine Oil Capacity: 14 quarts (3.5 Gal)
Engine Oil Type: Mobil Delvac 1300 Super 15W-40 or equiv
Hydraulic Fluid: Mobile DTE 10 Excel 46 or equiv
Radiator Fluid Type: Mobil Delvac Ex Life 50/50 Antifreeze
Air Pressure for Tires: 55 - 60 psi

Fuel Filter Replacement Part #: Kubota 1K947-43172
Oil Filter Replacement Part #: Wix 57430
Hydraulic Filter Replacement Part #: WIX A26A125T
Inner Air Filter Replacement Part #: WIX 49492
Outer Air Filter Replacement Part #: WIX 49491
Oil Separator Element Kit Part #: Kubota 1J508-05812