

LT 8x8 XHD



Specifications-Technical Data

Engine.....	DEUTZ TCD 3.6 L4 TIER 4 Diesel Engine	Fuel Capacity.....	20 Gal (US)
Drive System.....	Hydrostatic, Individual right-angle Gear Boxes	Towing Capacity.....	8,000 Lbs.
Water Propulsion.....	Hydraulically Driven Single Prop	Ground Pressure.....	0.9 – 3 PSI (w/wo tracks installed)
Hyd. Tank Capacity.....	20 Gal (US); Mobil DTE 10 Excel 46 or equiv.	Tracks.....	20" Industrial Rubber; Over-the-Tire
Electrical System.....	12 Volt with 90 Amp Alternator	Unit Dry Weight.....	7,200 lb
Battery.....	800 CCA (standard)	Payload Capacity.....	Land 3,000 lb; Water 1,600 lb
Park/Emergency Brake...	Hydraulic parking braking system	Seating	up to 6 Persons with optional seating
Instrumentation.....	Marine Grade Components	Land Speed.....	up to 13 MPH
Body Construction.....	3/16" and 1/8" Full-Weld Aluminum.	Speed in Water	up to 3.0 MPH
Bilge Pump.....	2200 GPH 12 Volt with Auto/Man. Switch	Ground Clearance...	11" w/ tracks, 10" wo tracks
Hydraulic Oil Cooler.....	Forced Air Hydraulic Cooler		

* October 2020

* Specifications subject to change with added options and without notice

Vehicle Dimensions: 205" L x 87" W x 90" H

Engine Oil Capacity: 8.45 quarts (2.11 gallons)
Engine Oil Type: Mobil Delvac 1300 Super 15W-40 or equiv
Radiator Fluid Type: Mobil Delvac Ex Life 50/50 Antifreeze
Air Pressure for Tires: 35 psi drive tires, 15 psi non-drive tires
Primary Air Filter Replacement Part #: Wix 46562
Safety Air Filter Replacement Part #: Donaldson P829333
Oil Filter Replacement Part #: Wix 57085
Fuel Filter Replacement Part #: Deutz Spin On 0412 0751
Hydraulic Filter Replacement Part #: SF-6620 & SF-6704-MG
Water Separator Filter Replacement Part #: Wix WF10175