

# LT 8x8 XHD



## Specifications-Technical Data

**Engine**..... DEUTZ TCD 3.6 L4 TIER 4 Diesel Engine  
**Drive System**..... Hydrostatic, Individual right-angle Gear Boxes  
**Water Propulsion**..... Hydraulically Driven Single Prop  
**Hyd. Tank Capacity**.....20 Gal (US); Mobil DTE 10 Excel 46 or equiv.  
**Electrical System**..... 12 Volt with 90 Amp Alternator  
**Battery**..... Optima Blue Top 800 CCA  
**Park/Emergency Brake**... Hydraulic parking braking system  
**Instrumentation**..... Marine Grade Components  
**Body Construction**..... 3/16” and 1/8” Full-Weld Aluminum.  
**Bilge Pump**..... 2200 GPH 12 Volt with Auto/Man. Switch  
**Hydraulic Oil Cooler**..... Forced Air Hydraulic Cooler

**Fuel Capacity**..... 20 Gal (US)  
**Towing Capacity**..... 8,000 Lbs.  
**Ground Pressure**..... 0.9 – 3 PSI (w/wo tracks installed)  
**Tracks**..... 20” Industrial Rubber; Over-the-Tire  
**Unit Dry Weight**..... 6,000 lb  
**Payload Capacity**.... Land 3,000 lb; Water 1,600 lb  
**Seating** ..... up to 6 Persons with optional seating  
**Land Speed**..... up to 13 MPH  
**Speed in Water** ..... up to 3.0 MPH  
**Ground Clearance**... 11” w/ tracks, 10” wo tracks

\* January 2021  
 \* Specifications subject to change with added options and without notice

Vehicle Dimensions: 205” L x 87” W x 90” H

Engine Oil Capacity: 8.45 quarts (2.11 gallons)  
 Engine Oil Type: Mobil Delvac 1300 Super 15W-40 or equiv  
 Radiator Fluid Type: Mobil Delvac Ex Life 50/50 Antifreeze  
 Air Pressure for Tires: 35 psi drive tires, 15 psi non-drive tires  
 Primary Air Filter Replacement Part #: Wix 46562  
 Safety Air Filter Replacement Part #: Donaldson P829333  
 Oil Filter Replacement Part #: Wix 57085  
 Fuel Filter Replacement Part #: Deutz Spin On 0412 0751  
 Hydraulic Filter Replacement Part #: SF-6620 & SF-6704-MG  
 Water Separator Filter Replacement Part #: Wix WF10175