

XTB66



Specifications-Technical Data

Engine..... Kubota V2304-T 59 HP Turbo Diesel (Tier III)
Drive System..... Direct Drive, Closed Loop Hydrostatic, Two-Speed
Water Propulsion... .. Hydraulically Driven Dual 10” Bronze Props
Tri-Mode Drive..... Wheels Only, Props Only, or Props & Wheels
Electrical System..... 12 Volt with 90-Amp Alternator
Battery..... Optima Blue Top 800 CCA
Park/Emergency Brake... Hydraulic Parking Brake
Instrumentation..... Marine Grade Clusters, Hour Meter
Body Construction.. 3/16” and 1/8” Full-Weld Aluminum, Marine Grade
Bilge Pump..... 2200 GPH 12 Volt with Auto/Man. Switch
Hydraulic Oil Cooler..... 4200 CFM Dual Cooling System
Tires..... Supergrip RimGuard 29x12.5x15 NHS
Tire Pressure.....55 - 60 PSI

Fuel Capacity..... 13 Gal (US) Approx. 8 Hrs Run Time
Towing Capacity..... 5,000 lb.
Ground Pressure..... 1.56 PSI Unloaded; 2.00 PSI Full Load
Hyd. Tank Capacity 13 Gal (US); Mobil DTE 10 Excel 46
Unit Dry Weight..... 5,800 lb. (2,630 kg)
Payload Capacity..... Land 1,600 lb. (725 kg); Water 1,200 lb. (544 kg)
Seating Up to 6 Persons including Operator
Land Speed..... 12 MPH (19.3 kph)
Speed in Water 3.5 MPH (5.6 kph)
Ground Clearance... 25” (Center of Hull)
Tracks 24” Industrial Rubber (domestic) /
20” Industrial Rubber (international)

Dimensions (US): 168” L x 95” W x 101” H

Dimensions (mm): 4,267 L x 2,413 W x 2,565 H

Vehicle will load on DOT approved deck-over, pintle hitch /bumper pull or gooseneck trailer; will load into 40’ HQ Container

* January 2021

* Specifications subject to change with added options and model updates